



Model: KNZD-42VR

KNZD-42VR Video Door Phone offers a full digital network and KOON VoIP solution for the secure access control and monitoring of a building entrance. This advanced Door phone supports SIP 2.0 and operators of IMS platform guaranteeing easy customization for telecom operators and service providers.

Features:

- SIP V1/V2(RFC2543/RFC3261)
- One speed dial Key
- Integrated RFID card reader
- Integrated Numeric Keypad
- DTMF Switch control
- Door Opening:
Keypad for password / RFID / Remote

Benefits:

- Compatibility**
supports SIP 2.0 and operators of IMS platform, effective interconnection and interworking with the mainstream IPPBX manufacturers
- High-end chip**
Equipped with the latest Broadcom's chip set
- Carrier standard voice**
Full duplex hands-free speakerphone, carrier standard voice
- Flexible of lock approach**
passwords , RFID card and DTMF Switch control
- A key to call**
One Speed dial Key

•Multiparty calls

- Holding/waiting 3 ways call/conference
- Easy installation**
integration into the existing LAN
- visitors leave a message**
Provide access to the message and playback message through the SIP phone
- Simple maintenance**
support online software upgrades and web management way
- Protective level**
Ip53 ,resistivity against dust, water, and mechanical damage

Target Groups:

Business: offices, shopping areas
Education: universities, campuses, schools, sports areas
Healthcare: hospitals, laboratories, Pharmaceutical factory

Logistics & Transportation: airports, parking lots or garages
Industries: factories, product center

Technical Parameters:

Signalling protocol

SIP 2.0(RFC3261)

Interface

Power supply 12V±15%/1A DC

Buttons

Quick dial buttons Buttons are made of stainless steel material, strong and durable.

Number of speed dial buttons 1

Numeric keypad touch buttons

Audio

Microphone 1

Loudspeaker 1W

Hands-free full-duplex support

Audio stream

Support protocol RTP

Codecs PCMA

RFID

EM-40XX(125KHz)

WAN

The recommended cable Super five or more

Relay outputs NC/NO contacts, max 30V/1AAC/DC

Active relay output 12V/500mA DC

Mechanical

Cover material Aluminum alloy cover, plastic pan

Operating temperature range 0°C – 55°C

Storage temperature range -40°C – 70°C

Relative humidity 10% - 95% (not condensing)

Installation Embedded installation

External dimensions 174.5×96×44 mm

Protection level IP53

Camera

Sensor 1/4" colour CMOS

Picture frequency Up to 30 snaps/s

Viewing angle 135° (H), 109° (V)

Resolution 640 (H) x 480 (V)

Sensitivity 1.9 V/lux-sec (550nm)

Infrared illumination Yes

KNZD-42 Voice Door Guard inherits the characteristics of the bearing VoIP products ,and it can be effective interworked with the mainstream IPPBX manufacturers,like Cisco、Avaya、3CX、Asterisk、BroadSoft.

